



# MPCV855M

The versatile expandable multimedia computer

This totally silent DIGITAL-LOGIC computer for display applications operates on the basis of the Intel® Processor® 800MHz with passive cooling. The main focus is on the two LAN ports, the service-friendly hard drive/CompactFlash, the video interfaces (DVI, QVGA, LVDS), the 6-channel audio output (SPDif) and the expansion with 2 PC/104-Plus cards. All three of the most popular computer video outputs are available.

A maximum of two different images can be optionally displayed on the existing video outputs. Two internal PC/104-Plus (ISA and PCI) slots are available for functional expansions. There are 3 connector openings (X1, X2 and X3) in the replaceable front panel for cabling additional functions. The power is supplied from the connecting terminals. 24 programmable I/O lines are available for control purposes.

#### Applications:

- \_ Display computer
- \_ POS, POI
- \_ Multimedia applications



## Ordering information

Item	No.	Description
MPCV855M	815020	with SM855-120 (800 MHz), 40GB-HD, COM 1/2, LPT, DVI, sound
Item	No.	Description
Upgrade	815060	256 to 512MB memory
	815062	256 to 1GB memory
Item	No.	Description
Downgrade	815050	1x CompactFlash holder instead of hard drive
Item	No.	Description
Option	815080	WLAN – 802.11 b/g
	815070	Adapter 220/110V 90W

## Technical data

### MPCV855M

<b>CPU</b>	Intel® Processor® C120, 800MHz
<b>2<sup>nd</sup> Level Cache</b>	0kB
<b>Chipset</b>	Intel® 855GME
<b>Memory</b>	256MB (max. 1GB)
<b>Ext. temp. hard disk</b>	40GB, 2.5" (max. 80GB)
<b>Optical drive</b>	-
<b>Video controller</b>	Intel® 855GME
<b>Video memory</b>	64MB
<b>3D-Support</b>	DirectX 9
<b>Video interface 1</b>	QXGA
<b>Video interface 2</b>	DVI, 24-bit
<b>Video interface 3</b>	LVDS, 18-bit
<b>Resolution</b>	2048 x 1536 (@ 75Hz)
<b>Keyboard, mouse</b>	USB
<b>Serial interface COM1</b>	RS232C
<b>Serial interface COM2</b>	RS232C
<b>Serial interface COM3</b>	-
<b>Serial interface COM4</b>	-
<b>Parallel interface</b>	-
<b>USB V2.0</b>	4x
<b>Firewire IEEE1394</b>	-
<b>TV input/Frame grabber</b>	-
<b>LAN Port A (with LAN boot)</b>	100/10Base-T (RJ45)
<b>LAN Port B</b>	1GB (RJ45)
<b>LAN Port C</b>	-
<b>SCSI</b>	-
<b>Audio controller</b>	AC97-2.3
<b>Line output</b>	Stereo
<b>Line input/mic.</b>	Stereo
<b>SPDif output</b>	yes, optical
<b>Option 1</b>	WLAN MiniPCI
<b>Option 2</b>	-
<b>Option 3</b>	-
<b>Option 4</b>	-
<b>Digital input/output</b>	24 programmable I/O
<b>Remote power on/off</b>	-
<b>Voltage input/power</b>	10V-30V DC / typ. 18W
<b>Plug-in power supply</b>	110/220V AC
<b>Expansion</b>	MiniPCI, PC/104-Plus (max. 2 cards)
<b>Power save function</b>	Suspend/Resume, SoftOff, Instant On
<b>Conformity</b>	CE, FCC
<b>Protection class</b>	IP40
<b>Size (W x L x H in mm)</b>	292 x 146 x 83
<b>Weight</b>	3 kg
<b>Housing</b>	Metal
<b>Colour</b>	grey/red
<b>Noise level</b>	<20dB(A)
<b>Operating temperature</b>	+5°C to +50°C
<b>Extended operating temperature</b>	-
<b>Vibration/shock incl. HD/CD/DVD</b>	1/10G
<b>MTBF</b>	60'000 hrs.
<b>Operating systems</b>	WIN2000, WIN XP, LINUX