


ICO300

Robust Din-rail Fanless Embedded System with Intel® Atom™ Processor E3815/E3827, 4 COM, 2 LANs, DIO and RTC




Specifications

Standard Color	White																		
Construction	Extruded aluminum and heavy-duty steel, IP40																		
CPU	Intel® Atom™ processor E3815 (1.46 GHz) or E3827 (1.75 GHz)																		
System Board	SBC87842																		
System Memory	DDR3L-1066 MHz SO-DIMM up to 4 GB (E3815) or up to 8 GB (E3827)																		
BIOS	AMI UEFI BIOS																		
System I/O Outlet	<table border="1"> <tr> <td>Serial Port</td> <td>4 x RS-232/422/485 (COM 1~4) Interface select by BIOS Supports Auto Flow Control in RS-485 mode</td> </tr> <tr> <td>USB</td> <td>2 x USB 2.0</td> </tr> <tr> <td>RTC</td> <td>Battery onboard</td> </tr> <tr> <td>Storage</td> <td>Supports 1 x CF (or mSATA*) Supports 1 x SATA SSD (or HDD)</td> </tr> <tr> <td>LAN</td> <td>2 x 10/100/1000 Mbps Ethernet (Intel® i211-AT for ICO300) (Intel® i210-IT for ICO300-WT)</td> </tr> <tr> <td>VGA</td> <td>1 x DB15 connector</td> </tr> <tr> <td>DIO (ICO300-DIO)</td> <td>1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming</td> </tr> <tr> <td>Power Input</td> <td>1 x DC power input with terminal block</td> </tr> <tr> <td>Wireless</td> <td>1 x full size PCI Express Mini Card slot supports wireless (3G/GPRS or Wi-Fi) 1 x SIM socket 2 x Antenna</td> </tr> </table>	Serial Port	4 x RS-232/422/485 (COM 1~4) Interface select by BIOS Supports Auto Flow Control in RS-485 mode	USB	2 x USB 2.0	RTC	Battery onboard	Storage	Supports 1 x CF (or mSATA*) Supports 1 x SATA SSD (or HDD)	LAN	2 x 10/100/1000 Mbps Ethernet (Intel® i211-AT for ICO300) (Intel® i210-IT for ICO300-WT)	VGA	1 x DB15 connector	DIO (ICO300-DIO)	1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming	Power Input	1 x DC power input with terminal block	Wireless	1 x full size PCI Express Mini Card slot supports wireless (3G/GPRS or Wi-Fi) 1 x SIM socket 2 x Antenna
Serial Port	4 x RS-232/422/485 (COM 1~4) Interface select by BIOS Supports Auto Flow Control in RS-485 mode																		
USB	2 x USB 2.0																		
RTC	Battery onboard																		
Storage	Supports 1 x CF (or mSATA*) Supports 1 x SATA SSD (or HDD)																		
LAN	2 x 10/100/1000 Mbps Ethernet (Intel® i211-AT for ICO300) (Intel® i210-IT for ICO300-WT)																		
VGA	1 x DB15 connector																		
DIO (ICO300-DIO)	1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming																		
Power Input	1 x DC power input with terminal block																		
Wireless	1 x full size PCI Express Mini Card slot supports wireless (3G/GPRS or Wi-Fi) 1 x SIM socket 2 x Antenna																		

Features

- Fanless design
- Supports Intel® Atom™ processor E3815 (1.46 GHz) or E3827 (1.75 GHz)
- 4 RS-232/422/485 ports
- Supports Windows® 10 IoT Solution
- 2 isolated 10/100/1000Mbps Ethernet ports
- 1 DIO port
- Supports wireless (3G/GPRS or Wi-Fi)
- Supports 1 CF (or mSATA) and SATA SSD (or HDD)
- Wide range 12 - 24V DC-In



Watchdog Timer	255 levels, 1~255 sec.
System Indicator	Power, Active
Power Supply	Power Input Range : 12-24VDC Power Input Rating : 12-24VDC, 1.21-0.66A (ICO300-E3815) 12-24VDC, 1.42-0.74A (ICO300-E3827) Power Protection : DC Version, OVP, Reverse protection
Operating Temperature	-20°C ~ +70°C (-4°F ~ +158°F)
Storage Temperature	-40°C ~ +85°C (-40°F ~ +185°F)
Humidity	10% ~ 95%
Vibration Endurance	2g@5-500Hz, amplitude 0.35 mm (operation/storage/transport)
Weight (net/gross)	1.0 kg (2.2 lb)/1.50 kg (3.3 lb)
Certificate	CE, FCC
Dimensions	48 mm (1.88") (W) x 110 mm (4.33") (D) x 155 mm (6.1") (H)
EOS Support	Windows® 7 Embedded Windows® 8 Embedded Linux support package Windows® 10 IoT core pro

* mSATA and wireless can be either one.

** mSATA and CF can be either one.


Ordering Information

Standard	
IC0300-E3815-DC	Robust din-rail fanless embedded system with Intel® Atom™ processor E3815 1.46 GHz and 4 COM ports (-20°C ~ +70°C)
IC0300-E3815-WT-DC (Optional)	Robust din-rail fanless embedded system with Intel® Atom™ processor E3815 1.46 GHz and 4 COM ports (-40°C ~ +70°C)
IC0300-E3827-DC	Robust din-rail fanless embedded system with Intel® Atom™ processor E3827 1.75 GHz and 4 COM ports (-20°C ~ +70°C)
IC0300-E3815-DIO-DC	Robust din-rail fanless embedded system with Intel® Atom™ processor E3815 1.46 GHz, 4 COM ports and DIO (-20°C ~ +70°C)
IC0300-E3827-DIO-DC	Robust din-rail fanless embedded system with Intel® Atom™ processor E3827 1.75GHz, 4 COM ports and DIO (-20°C ~ +70°C)

Optional	
CompactFlash™	4 GB or above (with W.T. CF)
2.5" SATA SSD or HDD (with W.T. SSD or HDD)	
DDR3L SO-DIMM	2 GB ~ 8 GB (with W.T. memory)
Wall mounting kit	
Wireless (3G/GPRS or Wi-Fi) module	

* Specification and certifications are based on requirements and may vary.

Dimensions



Overview

Embedded Systems

Embedded Systems for Transportation

3

Embedded Field Controllers

Industrial Firewall

Digital Signage Solutions

Embedded MicroBoxes

Industrial Barebone Systems

Industrial Chassis

Backplanes

Power Supplies

Peripherals & Accessories

