



Specification	
Description	21.5" IPS Full HD 1920×1080 3G -SDI HDMI Pro Broadcast Monitor
Model	4K215-9HSD-192 (4K215-9HD-192: W/O SDI)
Screen size	21.5" IPS
Display Colors	16.7M (8-bit)
Resolution	1920x1080 pixels
Dot pitch	248.25x248.25 um
Aspect Ratio	16:9
Brightness	250cd/m ²
Contrast Ratio	3000:1
Backlight	LED
Response Time	Tr + Tf=25ms
Viewing Angle	89°/89°(L/R) 89°/89°(U/D)
Inputs	3G-SDI, HDMI, YPbPr, Video, Audio(L/R), DVI-I, Tally, USB Upgrade
Outputs	3G-SDI, HDMI, YPbPr, Video
Audio	3.5mm Stereo Headphone, Speaker
SDI Support Format	480i/576i
	720p (60/59.94/50/30/29/25/24/23.98)
	1080i (60/59.94/50)
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)
HDMI Support Format	480i/576i/480p/576p
	720p (60/59.94/50/30/29/25/24/23.98)
	1080i (60/59.94/50)
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)
	4K UHD 3840×2160p (30/29.97/25/24/23.98Hz), 4096×2160p (24Hz)
Input Voltage	DC 9~24V
Power Consumption	≤15W
Working Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Unit Size	511.6Lx355.5Hx41.87D (mm) /535L×400H×100D(mm) (W/ Bracket)
Unit Weight	4.65kg/ 6.5kg(with bracket)

Advanced Features

- *Support 4K HDMI Input and Output
- *Peaking Focus Assist (Red highlight over parts of the monochrome image in focus)
- *Center Marker
- *Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1)
- *Image Freeze
- *Image Flip (H, V, H/V)
- *Camera 5D II Mode
- *Check Field (Red, Green, Blue, Mono)
- *Pixel to Pixel (Nonsupport in 4K input)
- *Zoom All (Nonsupport in 4K input)
- *U/D & L/R Zoom (Nonsupport in 4K input)
- *Aspect Ratio (Nonsupport in 4K input)
- *Color Temperature Adjustment
- *Built-in LED tally indicators (Red, Green, Yellow)

Standard Accessories	Optional Accessories	Packing Details	
3A DC Power Adapter	Anton Bauer Battery Plate	Box size	61x49x13.5CM
V-Mount Battery Plate	Suitcase	Per box G.W.	8.5KG
Mini HDMI Cable		Per Carton	1pc
Tally Kit		Carton Size	62.5x53x14.5CM
U bracket		G.W.	9KG
Operation Manual			