

Model Show: P133-9HSD (P133-9HD: W/O SDI )		Specification	
 	<b>Description</b>	13.3" Aluminum Design IPS Full HD 1920×1080 3G-SDI/ 4K HDMI Pro Broadcast Monitor	
	<b>Model</b>	P133-9HSD (P133-9HD: W/O SDI )	
	<b>Screen size</b>	13.3" IPS	
	<b>Display Colors</b>	16.7M	
	<b>Resolution</b>	1920×1080 pixels	
	<b>Dot pitch</b>	0.1533(H)×0.1533(V) mm	
	<b>Aspect Ratio</b>	16:9	
	<b>Brightness</b>	400cd/m <sup>2</sup>	
	<b>Contrast</b>	1000:1	
	<b>Backlight</b>	LED	
	<b>Response Time</b>	Tr + Tf=26ms	
	<b>Viewing Angle</b>	85°/85°(L/R) 85°/85°(U/D)	
	<b>Inputs</b>	3G-SDI, HDMI, YPbPr, Video, Audio(L/R), DVI-I, Tally, USB Upgrade	
	<b>Outputs</b>	3G-SDI, HDMI, YPbPr, Video	
	<b>Audio</b>	3.5mm Stereo Headphone, Speaker	
	<b>SDI Support Format</b>	480i/576i	
		720p (60/59.94/50/30/29/25/24/23.98)	
		1080i (60/59.94/50)	
	<b>HDMI Support Format</b>	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)	
		480i/576i/480p/576p	
720p (60/59.94/50/30/29/25/24/23.98)			
1080i (60/59.94/50)			
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
	4K UHD 3840×2160p (30/29.97/25/24/23.98Hz), 4096×2160p (24Hz)		
<b>Power Consumption</b>	≤12W		
<b>Input Voltage</b>	DC9~24V		
<b>Working Temperature</b>	-10°C~50°C		
<b>Storage Temperature</b>	-20°C~60°C		
<b>Unit Size</b>	315.5L×231H×26.4D mm (W/O Bracket)		
<b>Unit Weight</b>	1.64kg (W/O Bracket)/ 1.96kg (W/Bracket)		
<b>Advanced Features</b>			
*Support 4K HDMI Input and Output			
*Peaking Focus Assist (Red highlight over parts of the monochrome image in focus)			
*Center Marker			
*Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1)			
*Image Freeze			
*Image Flip (H, V, H/V)			
*Camera 5D II Mode			
*Check Field (Red, Green, Blue, Mono)			
*Pixel to Pixel (Nonsupport in 4K input)			
*Zoom All (Nonsupport in 4K input)			
*U/D & L/R Zoom (Nonsupport in 4K input)			
*Aspect Ratio (Nonsupport in 4K input)			
*Color Temperature Adjustment			
*Built-in LED tally indicators (Red, Green, Yellow)			
<b>Standard Accessory</b>		<b>Optional Accessory</b>	<b>Packing Details</b>
1.5A DC Power Adapter		DVI to VGA converter	<b>Box size</b> 37x34.7x10CM
V-Mount Battery Plate		Anton Bauer Battery Plate	<b>Per box G.W.</b> 2.86KG
Mini HDMI Cable		Suitcase	<b>Per Carton</b> 5pcs
Tally Kit			<b>Carton Size</b> 60.5x40.5x39 CM
Sunshade			<b>G.W.</b>
U bracket			
Operation Manual			