

Model Show P215-9HSD-CO	Specification			
	Description	21.5" IPS Full HD 1920×1080 3G -SDI HDMI Broadcast Carry-on Monitor		
	Model	P215-9HSD-CO		
	Screen size	21.5" IPS		
	Display Colors	16.7M (8-bit)		
	Resolution	1920x1080 pixels		
	Dot pitch	248.25x248.25 um		
	Aspect Ratio	16:9		
	Brightness	250 cd/m²		
	Contrast Ratio	3000:1		
	Backlight	LED		
Response Time	Tr + Tf=25ms			
Viewing Angle	89°/89°(L/R) 89°/89°(U/D)			
Inputs	3G/HD/SD-SDI,HDMI,Ypbpr, Video, Audio(L/R), Tally, USB Upgrade			
Outputs	3G/HD/SD-SDI,HDMI,Ypbpr, Video			
Audio	3.5mm Stereo Headphone, Speaker			
SDI Support Format	480i/576i			
	720p (60/59.94/50/30/29/25/24/23.98)			
	1080i (60/59.94/50)			
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)			
HDMI Support Format	480i/576i/480p/576p			
	720p (60/59.94/50/30/29/25/24/23.98)			
	1080i (60/59.94/50)			
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)			
Input Voltage	12V			
Power Consumption	≤15W			
Working Temperature	-10°C~50°C			
Storage Temperature	-20°C~60°C			
Unit Size	511.58Lx355.5Hx37.87D(mm) /590Lx410Hx260D(mm) (with suitcase)			
Unit Weight	4.25kg/ 14.5kg(with suitcase)			
	Advanced Features			
	*Peaking Focus Assist (Red highlight over parts of the monochrome image in focus)			
	*Center Marker			
	*Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1)			
	*Image Freeze			
	*Image Flip (H, V, H/V)			
	*Camera 5D II Mode			
	*Pixel-to-Pixel			
	*Check Field (Red, Green, Blue, Mono)			
	*Zoom All			
	*U/D & L/R Zoom			
	*Color Temperature Adjustment			
	*Built-in LED tally indicators (Red, Green, Yellow)			
Standard Accessories	Optional Accessories	Packing Details		
3A DC Power Adapter	Anton Bauer Battery Plate	Per Carton	1pcs	
V-Mount Battery Plate	U bracket	Carton Size	65.5x43x34CM	
Mini HDMI Cable		G.W.	15.6KG	
Tally Kit				
Suitcase				
Sunshade				
Operation Manual				

