



Model Show: P215-9HSD (P215-9HD: W/O SDI )	Specification			
 	<b>Description</b>	21.5" IPS Full HD 1920×1080 3G -SDI HDMI Pro Broadcast Monitor		
	<b>Model</b>	P215-9HSD (P215-9HD: W/O SDI )		
	<b>Screen size</b>	21.5" IPS		
	<b>Display Colors</b>	16.7M (8-bit)		
	<b>Resolution</b>	1920x1080 pixels		
	<b>Dot pitch</b>	248.25x248.25 um		
	<b>Aspect Ratio</b>	16:9		
	<b>Brightness</b>	250 cd/m²		
	<b>Contrast Ratio</b>	3000:1		
	<b>Backlight</b>	LED		
	<b>Response Time</b>	Tr + Tf=25ms		
	<b>Viewing Angle</b>	89°/89°(L/R) 89°/89°(U/D)		
	<b>Inputs</b>	3G/HD/SD-SDI,HDMI,Ypbpr, Video, Audio(L/R), Tally, USB Upgrade		
	<b>Outputs</b>	3G/HD/SD-SDI,HDMI,Ypbpr, Video		
	<b>Audio</b>	3.5mm Stereo Headphone, Speaker		
	<b>SDI Support Format</b>	480i/576i		
		720p (60/59.94/50/30/29/25/24/23.98)		
		1080i (60/59.94/50)		
	<b>HDMI Support Format</b>	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
		480i/576i/480p/576p		
		720p (60/59.94/50/30/29/25/24/23.98)		
		1080i (60/59.94/50)		
		1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
		4K UHD 3840×2160p (30/29.97/25/24/23.98Hz), 4096×2160p (24Hz)		
	<b>Input Voltage</b>	12V		
<b>Power Consumption</b>	≤15W			
<b>Working Temperature</b>	-10°C~50°C			
<b>Storage Temperature</b>	-20°C~60°C			
<b>Unit Size</b>	511.58Lx355.5Hx37.87D(mm) /535L×400H×100D(mm) (W/ Bracket)			
<b>Unit Weight</b>	4.25kg/ 6.12kg(with bracket)			
<b>Advanced Features</b>				
*Peaking Focus Assist (Red highlight over parts of the monochrome image in focus)				
*Center Marker				
*Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1)				
*Image Freeze				
*Image Flip (H, V, H/V)				
*Camera 5D II Mode				
*Pixel-to-Pixel				
*Check Field (Red, Green, Blue, Mono)				
*Zoom All				
*U/D & L/R Zoom				
*Color Temperature Adjustment				
*Built-in LED tally indicators (Red, Green, Yellow)				
<b>Standard Accessories</b>		<b>Optional Accessories</b>	<b>Packing Details</b>	
3A DC Power Adapter	Anton Bauer Battery Plate	<b>Box size</b>	61x49x13.5CM	
V-Mount Battery Plate	Suitcase	<b>Per box G.W.</b>	8.5KG	
Mini HDMI Cable		<b>Per Carton</b>	1pc	
Tally Kit		<b>Carton Size</b>	62.5x53x14.5CM	
U bracket		<b>G.W.</b>	9KG	
Operation Manual				