




### 7" FHD 4K Camera-top IPS Monitor

- 1920x1200 Resolution, 450cd/m<sup>2</sup> Brightness
- HDMI Input and Output
- Support 4K HDMI UHD
- 160° Wide Viewing Angles
- 22.95mm Thickness Ultra Thin Design
- False Color, Exposure, Check Field, Zoom



## PRODUCT DESCRIPTION



## FEATURE

- False Color
- Embedded Audio
- Zoom-in
- Pixel-to-Pixel
- Image Flip
- Check Field
- Screen Marker
- Nine Grid
- Exposure
- Camera Mode
- Image Freeze
- Center Marker
- Screen Marker
- Color Temperature Adjustment

### Peaking

The operator adjusts the focus control until the red outlines on the desired area are clear, indicating optimal focus. For the best results, be sure the subject is properly exposed. Enjoy taking your photos!



Subject in focus with Filter off



Subject in focus with Filter on



Subject out-focus with Filter off



Subject out-focus with Filter on



### Check Field

Check field function has 4 modes: Mono, R, G, B.



### Embedded Audio

The Audio Level Meters provide numerical indicators and headroom levels. It can generate accurate audio level displays to prevent errors during monitoring. The audio meter is green, and will turn yellow when exceeds -20dB, and turn red when exceeds -9dB.



## SPECIFICATIONS/ACCESSORIES

### Specifications

|                       |                                      |
|-----------------------|--------------------------------------|
| Model No.             | CHO730                               |
| Panel                 | 7"IPS                                |
| Resolution            |                                      |
| Brightness            | 450cd/m <sup>2</sup>                 |
| Contrast              | 1200:1                               |
| Viewing Angle         | 80°/80°(L/R)80°/80°(U/D)             |
| Input                 | HDMI                                 |
| Output                | HDMI                                 |
| Audio Out             | Stereo Headphone, Speaker(built-in)  |
| Input Voltage         | DC 7-24V                             |
| Battery Plate         | F970(Standard); D28S/D54, LP-E6, U60 |
| Power consumption     | ≤8W                                  |
| Power Connector       | DC                                   |
| Operating Temperature | -20°C~55°C                           |
| Storage Temperature   | -30°C~65°C                           |
| Install Way           |                                      |
| Dimension             |                                      |
| Weight                | 280g/310g(With F970 Battery Plate )  |

### Format

|             |  |
|-------------|--|
| HDMI Input  | 480i/576i/480p/576p                                  |
|             | 1080i(60/59.94/50)                                   |
|             | 720p(60/59.94/50/30/29/25/24/23.98)                  |
|             | 1080p(60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF) |
| HDMI Format | 4K UHD 3840X2160p(30/29/25/24/23.98)                 |
|             | 480i/576i/480p/576p                                  |
|             | 1080i(60/59.94/50)                                   |
|             | 720p(60/59.94/50/30/29/25/24/23.98)                  |
|             | 1080p(60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF) |
|             | 4K UHD 3840X2160p(30/29/25/24/23.98)                 |

### Standard Accessories



### Optional Accessories

