



# LCD Camera Monitor with SDI, HDMI & YPbPr Input

CL1013HBY --- YPbPr

CL1013SDI --- HD-SDI

Specific LCD Monitor by NEWAY Uses for Full HD Video Camera  
Seizing much more clear world  
Application for Full HD Video Camera in CCTV Monitoring and Making Movies



HD-SDI, HDMI & YPbPr Input,  
to connect with Full HD Video Camera

LCD 16:9 Aspect Ratio,  
max 1920×1080 pixels

To connect with Full HD Video Camera,  
as sub-monitor when CCTV Monitoring  
or Making Movies

Multi mounting methods to  
view under different angles



## Parameter

|                     |  |
|---------------------|--|
| Panel Size          | 10.1" TFT LCD (16:9)                             |
| Resolution          | 1024×600, support up to 1920×1080                |
| Brightness          | 250cd/m <sup>2</sup>                             |
| Contrast            | 500:1  |
| Viewing Angle       | 140°/ 110°(H/V)                                  |
| Input Voltage       | DC 12V (XLR DC Connection)                       |
| Input Signal        | SDI, HDMI, YPbPr, AV1/AV2                        |
| SDI/HDMI/YPbPr Mode | 480i/p, 576i/p, 720p, 1080i(50/60), 1080p(50/60) |
| Color System        | PAL / NTSC                                       |
| Current             | 500mA (under 800*600-60Hz)                       |
| Standby Current     | ≤50mA  |
| Power Consumption   | ≤6W  |
| Audio Output        | ≥250mW   |
| Speaker             | ×1(back)   |
| Ear Phone Slot      | ×1   |
| Mounts Process      | Standard VESA (75mm) Sockets                     |
| Size:(LWD)          | 259 x 170 x 36.5mm                               |
| Weight              | 1144g  |



## Accessories

12V1.5A DC adapter  
Remote control  
Manual  
HDMI to mini HDMI cable (optional)

