

7 Inch TFT LCD Monitor with SDI & YPbPr

CL7679SDI: HD-SDI, YPbPr, HDMI, AV input

CL7679HBY: YPbPr, HDMI, AV input



Advanced Features

Embedded Audio, Aspect Ratio, PIP, Dual-Screen ,
Underscan, Safe Markers, Color Temperature Settings,
Blue Only , H/V Delay, Built-in Speaker, TALLY, User Presets,
Safe & Area Marker, Headphone.



Aspect Ratio,
PIP, Dual-Screen,





- ① V-mount Plate
- ② Anton Bauer Gold Mount Plate(optional)



Specification

Screen Size: 7"

Dot Resolution: 800 x 480 pixels

Brightness: 450 cd/m²

Dot Resolution: 1024 x 600 pixels (Optional)

Brightness: 250 cd/m² (Optional)

Contrast Ratio: 500:1

Aspect Ratio: 16:9/4:3(adjustable)

Color 16.7M-Ture color

Color System:PAL/NTSC

Viewing Angle: 140° ,120° (H,V)

Input Voltage: DC6V-14V± 15%

Input signal: SDI, HDMI, COMPONENT, VIDEO, AUDIO

Out Signal: SDI,COMPONENT,VIDEO,AUDIO

Unique feature TALLY , Image Multiplication , Image Freeze

Power Consumption: ≤ 10W

Storage Temperature: -30°C ~ 80°C

Unit Size: 205L × 145W × 51H(mm)

Unit Weight: 700g



Functions

Remark

Composite in	BNC X 1 line
Component(Y/Pb/Pr) in	BNC X 1 line
SD-SDI in	BNC X 1 line
HD-SDI in	BNC X 1 line
HDMI in	1 line
Audio in	RCA X 1 line (dual channel)
Audio monitoring	Front speakers 0.5W (8Ω)
SDI embedded audio	PPM / UV
Composite out	BNC X 1 line
Component (Y/Pb/Pr) out	BNC X 1 line
SD-SDI out	BNC X 1 line
HD-SDI out	BNC X 1 line
TALLY	Red / green two color

ACCESSORIES

FC CE RoHS E-Mark



12V 3A DC adapter



Mini HDMI Cable



SDI Cable



BNC Cable



BNC to RCA Connector 3PCS



TALLY indicator adapter kit



V-Mount Plate



Anton Bauer Gold Mount Plate (optional)



Shoe mount



Sunshade



Manual