

10.4" TFT LCD Monitor



Model No. SEF104C-LUH

Ultra-Bright 10.4" VGA TFT LCD Touch Monitor, With High Resolution

Feature:

XGA 1024 x 768 pixels Resolution

High Contrast 1200:1

Ultra Brightness 1000 nits

Fast Response Time(Ton+Toff average 25 ms)

Industrial Application Panel with long product life cycle

Wide Viewing angle: 176(H)/176(V) Super MVA technology

One VGA Input

Three Video Inputs

Two Audio Inputs

USB Interface

Touch Screen Function

Built-In Speaker

Auto Power On function for VGA Signal

Auto Reversing Function for Video # 3

Auto Dimmer Function

NTSC/PAL Auto Switching

Optional: 1)Sunlight Readable Function: SEF104C-SLUH

2) DVI function: SEF104C-LUH-D

3) DVI+Sunlight Readable Function: SEF104C-SLUH-D

SEFORM ELECTRONICS CO., LTD.

TEL: 886-7-8130209 FAX: 886-7-8131917

E-mail: sales@seform.com.tw URL: www.seform.com.tw

10.4" TFT LCD Monitor

Specification

PANEL	Screen Size	10.4 inch (Diagonal)
	Display Resolution (dot)	1024 X RGB X 768
	Active Area (mm)	210.4(H) x 157.8 (V)
	Pixel Pitch (mm)	0.0685 (H) x 0.2055(V)
	Color Configuration	R.G.B. vertical stripe
	Display Colors	16.2M
	Backlight unit	LED
	Response time(Rise/Fall)	15/10 ms
	Contrast Ratio	1200:1
	Brightness	1000 nit
	View Angle(T/B/L/R)	88/88/88/88 deg.
	LED Life	50,000 Hr(min.)
	Power Rating	Input
Temperature	Operation(°C)	-30~+70
	Storage(°C)	-30~+80
TouchKit Driver	Windows vista / 9X / Me / NT4.0 / 2000 / XP / CE.NET/CE 2.12/3.0 Embedded/ Dos Mac OS 9X / OS X(Intel CPU) Linux Readme / Mandrake / Red Hat / Fedora Core / SuSE / Debian / (K)Ubuntu / Yellow Dog	
Accessories	VESA Stand x 1, Touch Stylus Pen x 1, AC/DC switching power supply x 1, Car cigarette lighter adapter x 1, remote controller x 1, users manual x 1, All-In-One Cable x 1, Touch Kit Driver x 1	


Mechanical drawing:

SEFORM ELECTRONICS CO., LTD.

TEL: 886-7-8130209 FAX: 886-7-8131917

E-mail: sales@seform.com.tw URL: www.seform.com.tw

10.4" TFT LCD Monitor



SEFORM ELECTRONICS CO., LTD.

TEL: 886-7-8130209 FAX: 886-7-8131917

E-mail: sales@seform.com.tw URL: www.seform.com.tw