VBOX-3121

Intel Gen6 i7-6600U with HD Graphic 520 / 2 x LAN/ 2 x HDMI/ VGA with 3 x RS-232/ DC 9-36V Input In-Vehicle Computer

Features

- Intel Gen 6 Core i7-6600U
- Wireless support LTE, WLAN, GPS, GSM/GPRS, Bluetooth(Option)
- 9V 36V DC Power Input
- Smarter Vehicle Power Ignition for Variety Vehicle
- 4 x RS-232/422/485 (for i7 and i5)
- 2 x DI / 2 x DO (12V / 100mA)









Wide Range Wireless

Battery Backup

Taiwan Patent No. M447854

System	
CPU	Intel Gen 6 Core i7-6600U 2.6GHz up to 3.4GHz
	Intel Gen 6 Core i5-6300U 2.4GHz up to 3.0GHz
	Intel Gen 6 Core i3-6100U 2.3GHz
	Intel Gen 6 Dual Core 3955U 2.0GHz
Memory	1 x DDR4 SO-DIMM up to 16GB
Graphics	Intel HD Graphics
ATA	2 x Serial ATA ports with 6Gb/s HDD Transfer Rate
LAN Chipset	2 x Intel i210-AT Gigabit Ethernet
Watchdog	1 ~ 255 Level Reset
I/O	
Serial Port	4 x RS-232/422/485 (for i7 and i5)
	3 x RS-232/422/485 (for i3 and C1)
USB Port	2 x USB 3.0 and 1 x USB 2.0 Ports
LAN	2 x RJ45 Ports for GbE
Video Port	2 x HDMI/ 1 x VGA
GPIO Port	2 In and 2 Out (12V / 100mA)
Audio	Mic-in / Line-out
Expansion Bus	3 x Mini-card Slots
Antenna	4 x SMA-type External Antenna Connectors for LTE / WLAN/ UMTS / GSM / GPRS / GPS / Bluetooth
SIM Card Socket	2 x SIM Card Sockets Supported Onboard with eject
Power Requirement	
Power Input	9V - 36V DC Power Input
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery (UPS)	Internal Battery Kit for 10 Mins Operating (Optional) Patent No.: M447854 - Build-in Battery







Qualification	
Certifications	CE, FCC Class A, E-13
Storage	
Туре	1 x 2.5" Drive Bay for SATA Type Hard Disk Drive/SSD 1 x SATA DOM
Software	
Operating System	Windows 10, Ubuntu 16.04 64bit
Environmental	
Operating Temp.	-40 ~ 70°C (SSD), ambient w/ 0.6m/s airflow
Storage Temp.	-40 ~ 80°C
Relative Humidity	10% RH – 90% RH (non-condensing)
Vibration (random)	IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD
Vibration Operating	MIL-STD-810G, Method 514.6, Procedure I, Category 4
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Certifications	CE, FCC Class A, E-13
Mechanical	
Construction	Aluminum Alloy
Mounting	Wall-mount, VESA-mount, Din Rail Mounting Kit
Weight	1406 g
Dimensions	250 x 167.6 x 54 mm (for i7 and i5)
	182 x 167.6 x 40 mm (for i3 and C1)
Ordering Information	
Part Number	VBOX-3121-i7, VBOX-3121-i5, VBOX-3121-i3, VBOX-3121-C1
Description	Intel Gen6 i7-6600U with HD Graphic 520 / 2 x LAN/ 2 x HDMI/

Made in Taiwan

State of Origin

VGA with 3 x RS-232/ DC 9-36V Input In-Vehicle Computer