

WPC156

15.6" PORTABLE CARRY-ON DIRECTOR MONITOR


Sunlight Visible | Portable suitcase, ideal choice for outdoor filming



>> FEATURES

- 15.6" 1920x1080 full HD IPS screen
- Portable waterproof case, easily cope with various harsh shooting environments
- Intuitive buttons + new menu interface, more convenient to operate
- Custom 3D-LUT, preview film look
- With Waveform, Vector scope, RGB Histogram, Focus Assist, Monochrome etc. functions, can help you accurately exposure and focus every shot.
- With multiple 1/4 screw thread, can be mount wireless transmission and other device
- The bottom of case built-in metal bracket, can mount the monitor on the tripod
- Built-in speaker, stereo earphone output

>> Professional Auxiliary Tools, Help You Focus and Exposure Accurately



>> MULTIPLE POWER SUPPLY WAY

XLR connector

DC IN 12V





Sony V-mount battery plate

>> PARAMETERS

Description	15.6" High Bright Carry-on Broadcast Monitor
Model	WPC156
Screen size	15.6" IPS
Resolution	1920×1080 pixels
Display Colors	16.7M colors 8bits
Gamut	72% NTSC
Pixel pitch	0.17925(W) x 0.17925(H) mm
Aspect Ratio	16:9
Brightness	1000 cd/m ²
Contrast	1200:1
Backlight	LED
Response Time	Tr + Tf=30ms
Viewing Angle	89°/89°(L/R) 89°/89°(U/D)
Inputs	HDMI*2, SDI*1, USB2.0*1
Outputs	HDMI*2, SDI*1
Audio	3.5mm Stereo Headphone, Speaker
SDI Support Format	720p (60/59.94/50/30/29/25/24/23.98)
SDI支持格式	1080i (60/59.94/50)
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)
HDMI Support Format	480i/576i/480p/576p
	720p (60/59.94/50/30/29.97/25/24/23.98)
HDMI支持格式	1080i (60/59.94/50)
	1080p (60/59.94/50/30/29.97/25/24/23.98)
	4K 3840×2160p (30/29.97/25/24/23.98 Hz)
	4K 4096×2160p (24Hz)
Power Consumption	≤25W
Input Voltage	DC 12~24V
Operating Temperature	-0°C~50°C
Storage Temperature	-20°C~60°C
Waterproof Level of Case	IP67
Material of Case	PP alloy
Unit Size	479x387x210 (mm)
Unit Weight	about 9.8kg

>> STRUCTURE



>> PACKING LIST

					
Monitor	3A Power Adapter	Mini HDMI Cable	SDI Cable	V-mount Battery Plate (default to mount on device)	User manual



Zhangzhou Seetec Optoelectronics Technology Co., Ltd

E-mail: sales@seetec.cn

Tel: +86-596-2182566

Website: www.feelworld.com.cn

Fax: +86-596-2672617

www.seetec.com.cn