Mid-Range Digital Signage Player



SI-613

6th Generation Intel[®] Core™ Processor-based Signage Player with Intel[®] HD Graphics 530 Integrated and Three HDMI





Signature Book TM



Specifications

System Mainboard	MBD613
CPU Type	Intel® Skylake-S DT processors (14nm monolithic) TDP ${<}{=}65W$
CPU Socket	LGA1151(Socket H4)
Chipset	H170/Q170 PCH
Memory	2x DDR4 2133 SO-DIMM, dual-channel, Max. 32GB
Graphics	Intel® HD integrated Graphics
LAN	1x Gigabit LAN
Expansion Slots	1x M.2 B key for storage/ Wi-Fi/ Bluetooth/ 4G/ LTE Wireless options 1x mPCle(x1) for Wi-Fi/ Bluetooth/ TV tuner/ 4G/ LTE options 1x SIM card slot
I/O Interface	3x HDMI 2.0 1x Gigabit LAN 2x USB 3.0 2x USB 2.0 1x RJ45 for RS-232 serial port 2x Audio connectors for Mic in / Line out Power / HDD LED, 1x power button 1x power jack connector
Auto Control and Monitoring	Watchdog Timer: 256 segments, 0,1,2255 (sec/min)
Power Requirement	
10wor Roquitor Horn	+12V DC
Construction	Aluminum + SGCC
Construction	Aluminum + SGCC
Construction Weight	Aluminum + SGCC 2.2kgs (4.85lbs)
Construction Weight Chassis Color	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white
Construction Weight Chassis Color Storage	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280)
Construction Weight Chassis Color Storage Power Supply	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280) 150W power adaptor
Construction Weight Chassis Color Storage Power Supply Mounting	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280) 150W power adaptor Slim design with wall mounting holes 215.6mm(W) x 215.6mm(D) x 40mm(H)
Construction Weight Chassis Color Storage Power Supply Mounting Dimensions Operating	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280) 150W power adaptor Slim design with wall mounting holes 215.6mm(W) x 215.6mm(D) x 40mm(H) 8.49"(W) x 8.49"(D) x 1.57"(H) (CPU TDP <=45W)
Construction Weight Chassis Color Storage Power Supply Mounting Dimensions Operating Temperature Storage	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280) 150W power adaptor Slim design with wall mounting holes 215.6mm(W) x 215.6mm(D) x 40mm(H) 8.49"(W) x 8.49"(D) x 1.57"(H) (CPU TDP <=45W) 0°C~40°C (32°F~104°F) (CPU TDP=65W)
Construction Weight Chassis Color Storage Power Supply Mounting Dimensions Operating Temperature Storage Temperature	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280) 150W power adaptor Slim design with wall mounting holes 215.6mm(W) x 215.6mm(D) x 40mm(H) 8.49"(W) x 8.49"(D) x 1.57"(H) (CPU TDP <=45W) 0°C~40°C (32°F~104°F) (CPU TDP=65W) -20°C ~ 80°C (-4°F~176°F)
Construction Weight Chassis Color Storage Power Supply Mounting Dimensions Operating Temperature Storage Temperature Relative Humidity	Aluminum + SGCC 2.2kgs (4.85lbs) Black & white 1x NGFF M.2 M key 22 x 80mm (2280) 150W power adaptor Slim design with wall mounting holes 215.6mm(W) x 215.6mm(D) x 40mm(H) 8.49"(W) x 8.49"(D) x 1.57"(H) (CPU TDP <=45W) 0°C~40°C (32°F~104°F) (CPU TDP=65W) -20°C ~ 80°C (-4°F~176°F) 5~90% @ 45°C, (non-condensing)

Features

- iSMART- for auto-scheduler and power resume
- iAMT (11.0), TPM 1.2, vPro and Watchdog timer
- Supports 6th Generation Intel[®] Core[™] processors
- Integrated Intel® HD Graphics 530
- 3x HDMI 2.0 built with Hardware EDID emulation function
- 2x DDR4 2133 SO-DIMM, dual-channel, Max. 32GB
- 1x M.2 B-Key & 1x mPCle(x1) + 1x SIM card slot, Wi-Fi, Bluetooth, 4G/LTE or TV tuner options
- Slim and segregated ventilation design

Ordering Information

	ł
SI-613-Q6700	i
	4

Book-Size Signage Player with MBD613 with Intel[®] Core™ 17-6700 processor (8M Cache, up to 4.00 GHz), 2x 4GB DDR4 2133 SO-DIMM memory, 64GB M.2, 150W power adaptor.

Dimensions

