



# WP-T21

Health Information Systems (HIS)

## Features

- Onboard Intel® Elkhart Lake Celeron J6412 & Alder lake-P i3, i5.
- 10 points PCAP multi-touch support.
- 3 x USB3.1, 3 x USB 2.0, 2 x COM, 1 x DP (by USB-C), 1 x LAN, 1 x RJ11 Cash Drawer
- Intel F/W TPM.
- Front IP65 spill resistance, Fanless System & VESA Compliance.
- WiFi/BT module (Project based).



## Specification

Model Name		WP-T21	
Mother Board		PE24	PE26
System Information	Processor	Intel® Celeron J6412	Intel® Alder Lake-P Platform i5-1235U @ 1.3GHz up to 4.4 GHz i3-1215U @ 1.2GHz up to 4.4GHz
	System Memory	1 x SO-DIMM DDR4 slot, 8GB RAM as standard. Max. memory support up to 16GB.	1 x SO-DIMM DDR5 slot, 8GB RAM as standard. Max. memory support up to 32GB.
	Intel AMT	N/A	i5 CPU only
	TPM		Intel F/W TPM 2.0
Display & Touch	LCD Size		21.5"
	Display Type		Full HD
	Resolution		1920x1080
	Luminance		250cd/m <sup>2</sup>
	Backlight		LED
	Touch Type		True-Flat PCAP multi-touch screen
Storage		1 x M.2 SSD	1 x M.2 SSD or 2 x 2.5" SSD for RAID 0/1 (Alder Lake-P Platform only, project based)
Expansion		1 x M.2 A,E Key (for WiFi/BT project based)	
Display	Graphic Chipset	Intel® UHD Graphics for 10th Gen Intel® Processors	Intel® Iris® Xe Graphics eligible
	USB Port		3 x USB 2.0 3 x USB 3.1
I/O	COM Port	2 x RJ-48 (Support DC+0/5/12V by BIOS default is 0V)	
	DP	1 x Type C (DP+PD)	
	Cash Drawer	1 x RJ11 (Support DC+12V or 24V(default)port, support 2 cash drawers)	
Audio	Speaker Output	2 x 2W	
Certification Information		CE / FCC Class A / LVD	
Ethernet	LAN Chipset	Gigabit-LAN: support WOL, PXE	
	Ethernet Interface	10/100/1000 Base-Tx GbE compatible	
	LAN Port	1 x RJ-45	
	DC Input Connector	4 pin DIN	
Power Requirement	Adapter	Input:100 ~ 240Vac/ 50 ~ 60Hz Output: 65W Adapter (19V Adapter) AC-DC Adapter	Input:100 ~ 240Vac/ 50 ~ 60Hz Output: 90W Adapter (19V Adapter) AC-DC Adapter
		Operating Temperature	0°C ~ 40°C
Mechanical & Environmental	Storage Temperature	-20°C ~ 60°C	
	Operating Humidity	10% ~ 90% Relative Humidity, Non-condensing	
	Weight	5.8 Kgs	
	IP Rating	Front IP65	
	Mounting Kit	Wall / Stand / VESA 75mm x 75mm	
	System Fan	Fanless	
	Construction - Front	Metal- White	
	Construction - Rear	Metal- White	
Dimension	509 x 305 x 48mm		
OS Support	Fanless	Yes	
		Windows 10/11 (64 bit), Linux(Ubuntu 22.04)	

## Contact

5F, No.59, Ln. 77, Xing-Ai Rd., Neihu Dist., Taipei City 114, Taiwan. R.O.C

+886 2 7721 4688    +886 2 7721 2289    sales@poindus.com