

WVP-T21 KDS

21.5" Light Industrial Panel PC



Features and Benefits

- / Onboard Intel® Elkhart Lake Celeron J6412 & Alder Lake i3 & i5.
- / 10 points PCAP multi-touch support.
- / 3 x USB3.1, 3 x USB 2.0, 2 x COM, 1 x DP (by USB-C), 1 x LAN, 1 x CD
- / Intel F/W TPM.
- / Front IP65, Fanless System & VESA Compliance.
- / WiFi/BT module (Project based).
- / Extension Module design (Project based).

Specification

Model Name		WP-T21	
System Information	Processor	Intel® Celeron J6412	Intel® Alder Lake-P Platform i5-1235U @ 1.3GHz up to 4.4 GHz i3-1215U @ 1.2GHz up to 4.4GHz
	System Memory	1 x SO-DIMM DDR4 slot, 8GB RAM as standard. Max. memory support up to 16GB.	1 x 8GB DDR5 SO-DIMM memory Max. support up to 32GB
	TPM		Intel F/W
	LCD Size		21.5"
Display & Touch	Display Type		Full HD
	Resolution		1920x1080
	Luminance		250cd/m ²
	Backlight		LED
	Touch Type		Projective Capacitive
	Touch Controller		USB touch
Storage			1 x M.2 SSD
Expansion			1 x M.2 M Key for SSD 1 x M.2 A,E Key (for WiFi/BT project based)
I/O	USB Port	3 x USB 3.1 3 x USB 2.0	3 x USB 2.0 3 x USB 3.1
	COM Port		2 x RJ-48 (Support DC+0/5/12V by BIOS default is 0V)
	DP		1 x DP (USB-C)
	Cash Drawer		1 x RJ11 (Support DC+12V or 24V(default)port, support 2 cash drawers
Audio	Audio Codec		Realtek
Speaker Output			2 x 2W
Certification Information			CE / FCC / LVD
Ethernet	LAN Chipset		Gigabit-LAN: support WOL, PXE
	Ethernet Interface		10/100/1000 Base-Tx GbE compatible
	LAN Port		1 x RJ-45
	DC Input Connector		4 pin DIN
Power Requirement	Adapter	Input:100 ~ 240Vac/ 50 ~ 60Hz Output: 65W Adapter (19V Adapter) AC-DC Adapter	Input:100 ~ 240Vac/ 50 ~ 60Hz Output: 90W Adapter (19V Adapter) AC-DC Adapter
	Operating Temperature		0°C ~ 40°C
Mechanical & Environmental	Storage Temperature		-20°C ~ 60°C
	Operating Humidity		10% ~ 90% Relative Humidity, Non-condensing
	Weight		5.8 Kg
	IP Rating		Front IP65
	Mounting Kit		Wall / Stand / VESA 100mm x 100mm
	System Fan		Fanless
	Construction - Front		Metal- black
	Construction - Rear		Metal- black
Dimension		509 x 305 x 48 mm	
OS Support			Yes
			Win 10, Linux



Contact

<http://www.poindus.com>

Poindus Systems Corp.

Taiwan (HQ) | Germany | UK | Iberica

5F., No. 59, Ln. 77, Xing-Ai Rd., Neihu Dist., Taipei City 114, Taiwan. R.O.C.

☎ +886 2 7721 4688 📠 +886 2 7721 2289 ✉ sales@poindus.com

Poindus
COMPAL GROUP